



LUBMOR Sp. z o.o.

ul. Wieleńska 1, 64-980 Trzcianka

tel. +48/67/216-22-44

fax +48/67/216-59-40

e-mail: marketing@lubmor.pl

e-mail: konstrukcja@lubmor.pl

GRP DOOR

**KI 24-90
00-019**

GRP DOOR

APPROPRATION

The single GRP door is designed for closing entrances to operating – theatres in hospitals or entrances to special accomodations , e.g. factory of medicines .

EXECUTION

The door – frame is made of 3 mm specially profiled steel plate .

Connection clips for fixing of the door in the wall are welded to the door – frame .

Door sill is protected by means of a stainless steel cover .

The door – leaf of „sandwich” construction is made of glass reinforced polyester resin (GRP) with core of rigid polyurethane foam .

The door is fitted with a lock with patent insert , brass hinges and vision panel of 6 mm thick glass pane .

A rubber sealing gasket is mounted around the door – frame . The fittings are nickel – chromium plated and polished .

DELIVERY RANG

Delivery set includes a complete door with additional elements for fixing of the door in the wall . These elements are delivered freely .

PACKING , TRANSPORT , STORAGE

The door is protected against mechanical damages can be displaced by means of the fork – lift trucks and the cranes when will be placed on pallets .

It can also be stored in rows and stacks in store accomodations .

DIVISION MARK AND FINISHING

Types :

- with mortise lock

S - with sanitary mortise lock

Varieties :

P - right hand door

L - left hand

The door – leaf is finished of polyester resin type gelcoat white colour .

The door – frame is painted of white stove paint .

EXAMPLE OF DESIGNATION

GRP door , clear opening H x B – 2021 x 800 , variety L – left hand.

GRP DOOR 2021 x 800 L acc. to information card no KI 24-90/00-019.