



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka

tel. +48/67/216-22-44

fax +48/67/216-59-40

e-mail: marketing@lubmor.pl

e-mail: konstrukcja@lubmor.pl

SHIP TRAPEZIAL WINDOW
Model NOW

KI 24-98
30-900

SHIP TRAPEZIAL WINDOW - Model NOW

APPROPRATION

Ship windows are designed for using on the water ships .

EXECUTION

Construction of the window corresponds with standards PN-84/W-88070 and ISO 3903 : 1993 (E) and Lubmor's technical drawing. The sizes A/B x H are included acc. to the customer's needs till now. It is possible making the windows of the other sizes.

The window is made of stable frame , cover and hardened glass pane . The frame is fixed with cover of screws and glass pane is sealed of silicone gasket . The window frame is protected against corrosion with epoxy primer . The place under silicone gasket is protected with painting set consisting three epoxy covers total thick. 100µm .

DELIVERY RANG

Delivery set includes a complete window .

PACKING , TRANSPORT , STORAGE

The glass pane is protected with foil and paraffin . This foil is removed after mounting the window on the ship .

The windows are delivered on the pallets without packing .The goods should be transported of dry , clean and lidded trucks in order to avoid dislocation,mechanical damages and the agents which might to cause the gasket damages.

The windows should be stored in closed accommodations where conditions are the same as in transpot .

DIVISION , MARKING

Window marking :

NO - non opened

W - with stable frame for welding

- three serial numbers indicate a kind of material of separate window elements successivelyas below :

- material of stable frame
- material of moving frame
- material of cover

Numeral equivalent of materials :

- 0 - the window no includes the element
- 1 - brass
- 2 - steel
- 3 - aluminium

- kind of glass pane :

Y1 - transparent glass pane made of polished or float glass

Y2 - one - side matt glass pane made of polished or float glass

EXAMPLE OF DESIGNATION

Ship window clear opening A/B x H – 520/585 x 750 , non opened with stable steel frame for welding , without moving frame , with brass cover , float and transparent glass pane thick. 12 mm acc . to catalogue card KK 24-00/30-900.

WINDOW 520/585 x 750 x ≠12 NOW 201 Y1 acc.to information card KI 24-98/30-900.

This catalogue card correspond with drawing no N 24-98/30-900.