



H	B	H1	B1	Mass (kg)
1500	500	1796	796	71
1650	650	1946	946	101
	800		1096	103
1800	650	2096	946	110
1850	800	2146	1096	116



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka
 tel. +48/67/216-22-44
 fax +48/67/216-59-40
 e-mail: marketing@lubmor.pl
 e-mail: konstrukcja@lubmor.pl

GRP COLD STORAGE DOOR

**KI 24-98
34-124**

GRP COLD STORAGE DOOR

APPROPRATION

Cold storage door is designed for closing the passages in cold chambers on floating and land objects .

This door can be used :

- with electrical heating system from minus 30°C to 0°C
- without electrical heating system above 0°C .

EXECUTION

The door frame and door leaf are made as a shell construction of glass fibre reinforced polyester resin . The door leaf is filled with rigid polyurethane foam , around a silicon seal is mounted in order to ensure door tightness .

The good has got a metal inserts \neq 6 mm for mounting of self – closing devices and knob for opening it by the person accidentally closed in chamber .

Standard door is fitted with : three hinges , closures with three – point clamp , inside and outside handle and hasp . These elements are made of stainless steel .

Heating system is mounted for the door used in accommodations of temperature below 0°C . This system (power 27 W) make impossible to freezing a seal and should be connected for wiring system 24 V .

DELIVERY RANG

Delivery comprises the door with all fittings but without of mounting holes and fixing elements .

PACKING , TRANSPORT , STORAGE

The door protected against mechanical damages can be loaded to containers .The goods placed on the pallets in quantity to 5 pieces with wooden separators beetwen them , can be displaced by means of the tracks and the cranes but must be stored in closed accommodations .

DIVISION , MARK AND FINISHING

Varieties :

- P - right hand door (as shown on the drawing)
- L - left hand door (as reflected)

Types :

- without heating system (no marked in designation)
- E - with heating system

All the door is finished of gelcoat colour white .

EXAMPLE OF DESIGNATION

Cold storage door size H x B – 1650 x 800 , variety P – right hand , with heating system – E .

GRP COLD STORAGE DOOR 1650 x 800 – P – E, acc. to information card
KI 24-98/34-124.