



H	B	Mass (kg)
1550	800	49
1650	650	49
	800	53
1750	800	57



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka
 tel. +48/67/216-22-44
 fax +48/67/210-19-19
 e-mail: lubmor@lubmor.pl
 www.lubmor.pl

GRP EXTERNAL DOOR

**KK 24-12
 34-210**

GRP EXTERNAL DOOR

APPROPRATION

The external door is designed for closing the pasageways form the open deck to the internal accomodations in all float objects . This door is suitable for mounting in metal partitions as a self – contained or combined door with heavy steel door .

EXECUTION

The door frame is made of 3 mm specially profiled steel plate . The door leaf of sandwich construction is made of glass fibre reinforced polyester resin (GRP) with a core of rigid polyurethane foam .

The door sill is protected by means of stainless steel cover .

The door is fitted with a brass lock with patent insert and removable stainless steel hinges .

This door can also be fitted with rectangular vision panel of hardened glass pane .

The fittings are nickel – chromium plated and polished .

DELIVERY RANG

Delivery comprises complete door with the fittings .

PACKING , TRANSPORT , STORAGE

The door protected against mechanical damages is adapted for transportation in containers and displaces by means of the trucks and the cranes if the doors are placed on pallets .

This door can also be stored in rows and stacks in store accommodations .

DIVISION , MARK AND FINISHING

Varieties :

L – left hand door

P – right hand door

Kinds :

o – with vision panel

(without the marking) – without vision panel

The door leaf is finished of polyester resin type gelcoat in standard colour white .

The door frame in painted of a primer .

EXAMPLE OF DESIGNATION

GRP external door with vision panel , clear opening H x B – 1750 x 800 , variety L – left hand .

GRP EXTERNAL DOOR 1750 x 800 L o acc. to catalogue card no KK 24-12/34-210.

This catalogue card corresponds with drawing no N 24-90/34-210.