



## LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka  
 tel. +48/67/216-22-44  
 fax +48/67/210-19-19  
 e-mail: lubmor@lubmor.pl  
 www.lubmor.pl

**GRP HATCH**

**KK 24-12  
 34-221**

# GRP HATCH

## APPROPRATION

GRP hatch is designed for using on all floating units as a hatchway closure from open decks.  
Hatch to be welded to steel wall.

## EXECUTION

Hatch – frame is made of flat thick. 8 mm.

Cover is made of glass reinforced polyester resin thick. 8 mm without insulation. The cover is fixed to the frame be means of stainless steel hinges. A grip of stainless steel is bolted to inside surface of cover.

## DELIVERY RANG

Delivery comprises a complete hatch.

## PACKING, TRANSPORT, STORAGE

Hatch is protected against mechanical damages. The goods of quantity up to 3 pcs placed on the pallets with wooden separators, can be displaced by means of the cranes and fork – lift trucks. They must be stored in roofed accommodations.

## DIVISION, MARKING

Varieties :

P - right hand hatch (acc.to drawing)

L - left hand hatch (as reflected)

Hatch – frame is protected of epoxy – zink paint thick. min. 40 µm.

Cover is finished of polyester resin type gelcoat in colour acc.to RAL catalogue.

## EXAMPLE OF DESIGNATION

GRP hatch variety right hand – P, with cover in white colour acc.to RAL 9003.

GRP HATCH P/9003 acc.to catalogue card no KK 24-12/34-221.

This catalogue card corresponds with drawing no N 24-98/34-221.