



\*For  $B > 800$

H	B	H1	B1	Mass (kg)
1600	900	1658	958	90,0
	700		758	85,0
1800	700	1858	758	93,0
	800		858	97,0
	900		958	101,0
1900	700	1958	758	96,0
	800		858	101,0
	900		958	107,0



## LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka  
 tel. +48/67/216-22-44  
 fax +48/67/210-19-19  
 e-mail: lubmor@lubmor.pl  
 www.lubmor.pl

**GRP SPLASH-TIGHT  
 EXTERNAL DOOR**

**KK 24-12  
 34-242**

# GRP SPLASH – TIGHT EXTERNAL DOOR

## APPROPRIATION

GRP splash – tight external door is designed for closing the passageways from the opened deck to the internal accommodations on all floating objects .

They are adapted for mounting in metal walls .

## EXECUTION

The door – frame is made of tee bar . It can be welded or screwed to the ship's wall .

The door – leaf has a shell construction and is made of glass reinforced polyester resins with inside filling of rigid polyurethane foam . At top of the door is installed steel stiffeners for fixing self-closers, hooks etc.

The door is equipped with lock with patent cylinder , stainless steel hinges and hardened glass pane thick. 10 mm . Window frame is also made of stainless steel . The screws fixing a glass pane in window are mounted from opposite side to hinges .

The door is splash – tight owing to toggles made of stainless steel .

## DELIVERY RANG

Delivery comprises the door with all fittings but without of fixing elements .

## PACKING , TRANSPORT , STORAGE

The doors protected against mechanical damages are adapted for transport in containers and displacing on pallets by means of the trucks and the cranes . They can also be stored in rows and stacks in store accommodations .

## DIVISION , MARK AND FINISHING

Varieties :

P - right hand door (as on the drawing)

L - left hand door (as reflected)

Kinds :

1 - without window

2 - with rectangular window 400 x 600

3 - with circular window  $\varnothing$  270

Types :

s - door – frame adapted for welding (without mounting holes)

p - door – frame adapted for screwing (with mounting holes)

Door – leaf is finished of white gelcoat .

Door – frame is primed for s – type and painted acc. to RAL catalogue for p – type .

## EXAMPLE OF DESIGNATION

GRP splash – tight external door size H x B – 1600 x 700 , right hand variety – P , with circular window – kind 3 , with door – frame adapted for screwing – type p , painted on colour RAL 9003.

GRP SPLASH – TIGHT EXTERNAL DOOR 1600x700 P-3-p/9003 acc . to catalogue card KK 24-12/34-242.

Above mentioned door corresponds with door acc. to KK 24-12/34-228.

This catalogue card corresponds with drawing no N 24-02/34-242.