



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka
tel. 067/216-22-44, fax 067/216-59-40

SANITARY UNIT

**KI 24-95
35-502**

SANITARY UNIT

APPROPRIATION

The sanitary unit with bath-tube is designed for mounting as a complete bathroom for service two neighbour cabins for crew or passengers on the ships.

EXECUTION

The body of the unit is made of 33 mm thick panels. These panels are made of galvanized steel sheet and filled of mineral wool. Inside cassettes thick 0,75 mm are covered PCV foil or ceramic tiles if they are made of 1,5 thick steel sheet. Outside cassettes have got thick 0,75 mm. Floor of the unit is made of steel plate of thick. 4 mm and protected both sides against corrosion and covered of ceramic antislip tiles.

Ceiling consist two galvanized steel sheet thick 0,75 mm with mineral wool as an inside insulation. Bottom cassettes of the ceiling are covered PVC foil or lacquered.

The doors mounted for the sanitary unit are executed of PVC covered steel sheet and filled of mineral wool or mineral plate covered of decorative plate.

The sanitary unit can be equipped with :

- wall hanged water-closet bowl
- wash basin with tap
- bath-tube with shower tap (thermostatic or not)
- ventilation exhaust Ø80mm/Ø100mm
- electric heater 400W or floor
- toilet paper holder + spare
- toilet cabinet or mirror
- wall light with socket
- storm grip
- towel hook
- coat hook
- sponge and soap basket
- soap holder
- toilet brush
- shower curtain
- others acc.to wishes

Pipes supplying hot and cold water are insulated against condensation on outside of the unit.

DELIVERY RANG

Delivery comprises a fully equipped sanitary unit suitable for connection to water and electrical systems.

The sanitary unit can be supplied as a monolithic construction or at the segments (for mounting on the place of destination).

PACKING, TRANSPORT, STORAGE

The sanitary units are packed of plastic foil and the doors are additional protected of fibreboard. It can be displaced by means of the fork-lift trucks or the cranes. They have to be stored in closed store accommodations.

DIVISION, MARKING, FINISHING

Varieties :

R - right as shown in drawing

L - left as reflected

Types :

I - as shown in drawing

II - as shown in drawing

Opening direction of the door :

A- L/R - door opened outside left or right hand

Equipment openable :

1 - wash basin

3 - bath-tube

5 - water closet bowl

Kind of flushing :

a - gravitational

c - vacuum system

EXAMPLE OF DESIGNATION

Sanitary unit size 1500x2250 left, type I with left hand door openable outside and with wash basin, bath-tube, water closet bowl, gravitational flushing.

SANITARY UNIT 1500x2250 -L-IA-L-135a acc. to **KK 24-02/35-502**.