



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka
 tel. 067/216-22-44, fax 067/216-59-40

SANITARY UNIT

**KI 24-95
 35-549**

SANITARY UNIT

APPROPRIATION

The sanitary unit with shower is designed for mounting as a complete bathroom for crew or passengers on the ships. Two units mounted together forming one sanitary complete pair. This sanitary unit can also be installed in land buildings.

EXECUTION

The body of the unit is made of 28 mm thick panels. These panels are made of galvanized steel sheet and filled of mineral wool. Inside cassettes thick 0,75 mm are covered PCV foil and thick 1,5 mm are ceramic files glued on. Outside cassettes have got thick 0,75 mm.

The floor made of steel plate is divided for shower part with scupper grating and general part. Floor surfaces are protected against corrosion. The floor is glued on antislip ceramic tiles or smooth ones with grating.

Ceiling consist two galvanized steel sheet thick 0,75 mm with mineral wool as inside insulation. Bottom cassettes of the ceiling are covered PVC foil or lacquered.

The doors mounted for the sanitary unit are executed of PVC covered steel sheet and filled of mineral wool.

The sanitary unit can be equipped with :

- | | |
|---|--------------------------|
| - wall hanged water – closet bowl
(gravitational or vaccum flushing) | - storm grip 2 pcs |
| - wash basin with tap | - towel hook 3 pcs |
| - shower tap (thermostatic or not) | - coat hook 2 pcs |
| - ventilation exhaust Ø 80 mm | - sponge and soap basket |
| - electric heater 300 W or floor heating | - soap holder |
| - toilet paper holder + spare | - toilet brush |
| - toilet cabinet or mirror | - shower curtain |
| - wall light with socket | - others acc. to wishes |

Pipes supplying hot and cold water are instalated against condensation in outside of unit. Inside pipes are nickel-chromium plated.

DELIVERY RANG

Delivery comprises a fully equipped sanitary unit suitable for connection to water and electrical systems. The sanitary unit can be supply as a monolith or at the segments for mounting on the place of destination.

PACKING, TRANSPORT, STORAGE

Sanitary units are packed of plastic foil and the doors additional of fibreboard. It can be displaced by means of the fork-lift trucks or the cranes. The must to be stored in closed store accommodations.

The sanitary units delivered in parties are packet at the wooden cases.

DIVISION, MARK, FINISHING

Varieties :

I - as shown in drawing

II - as reflected

Types :

A - floor sewer as shown in drawing

B - floor sewer as reflected

PVC colour and ceramic files onces acc. to order.

EXAMPLE OF DESIGNATION

The sanitary unit variety I- as shown in drawing, type A-floor sewer as shown in drawing.

SANITARY UNIT I-A acc. to information card no KI 24-95/35-549.