



LUBMOR Ltd.

ul.Wieleńska 1, 64-980 Trzcianka tel.067/216-22-44,fax 067/216-59-40 e-mail: lubmor@postdata.pl

SANITARY UNIT WC

KK 24-01 35-551

SANITARY UNIT WC

APPROPRATION

The sanitary unit WC is designed for mounting as a complete bathroom for service two neighbour cabins for crew or passengers on the ships.

This sanitary unit can also be installed in land buildings.

EXECUTION

The body of the unit is made of 33 mm thick panels. These panels are made of galvanized steel sheet and filled of mineral wool. Inside cassettes thick 0,75 mm are covered PVC foil or ceramic tiles if they are made of 1,5 thick steel sheet. Outside cassettes have got thick 0,75 mm. Floor of the unit is made of steel plate of thick. 4 mm and protected both sides against corrosion and covered of ceramic antislip tiles.

Ceiling consist two galwanized steel sheet thick 0,75 mm with mineral wool as an inside insulation. Bottom cassettes of the ceiling are covered PVC foil or lacquered.

The doors mounted for the sanitary unit are executed of PVC covered steel sheet and filled of mineral wool or mineral plate covered of decorative plate.

The sanitary unit can be equipped with:

- wall hanged water - closet bowl

- wash basin with tap

ventilation exhaust Ø80mm/Ø100mm

- electric heater 400W

- toilet cabinet or mirror

- others acc.to wishes

- storm grip

- towel hook

- soap holder

- toilet brush

- toilet paper holder + spare

- wall light with socket

Pipes supplying hot and cold water are insulated against condensation on outside of the unit. Inside pipes are nickel-chromium plated.

DELIVERY RANG

Delivery comprises a fully equipped sanitary unit suitable for connection to water and electrical systems.

The sanitary unit can be supplied as a monolithic construction or at the segments (for mounting on the place of destination).

PACKING, TRANSPORT, STORAGE

The sanitary units are packed of plastic foil and the doors are additional protected of fibreboard. It can be displaced by means of the fork-lift trucks or the cranes. They have to be stored in closed store accommodations.

The sanitary units delivered in parties are packet at the wooden cases.

DIVISION, MARKING, FINISHING

Varieties:

R - right as shown in drawing

L - left as reflected

Types:

I - as shown in drawing

II - as shown in drawing

Opening direction of the door:

A-L/R - door opened outside left or right hand

Equipment:

1 - wash basin

5 - water closet bowl

Kind of flushing:

a - grawitational

c - vacuum system

EXAMPLE OF DESIGNATION

Sanitary unit WC size 1100×1900 right, type I with left hand door opened outside and with wash basin, water closet bowl, grawitational flushing.

SANITARY UNIT WC 1100 x 1900 -R-IA-L-15a acc. to no KK 24-01/35-551.