



H	Hz	B	Bz	b
1800	1992	600	1682	881
1900	2092	700	1882	981
2000	2192	800	2082	1081
2050	2242	900	2282	1181
		1000	2482	1281
		1050	2582	1331



**LUBMOR Sp. z o.o.**

ul. Wieleńska 1, 64-980 Trzcianka  
 tel. +48/67/216-22-44  
 fax +48/67/210-19-19  
 e-mail: [lubmor@lubmor.pl](mailto:lubmor@lubmor.pl)  
[www.lubmor.pl](http://www.lubmor.pl)

**SLIDING DOOR  
 CLASS A0-A60**

**KK 24-12  
 34-771**

# SLIDING DOOR CLASS A0-A60

## APPROPRIATION

Sliding door class A0-A60 is designed for closing the passageways in fireproof partitions, engine and stairs of required fire protection from A0-A60 inside all floating or land objects.

The door to be welded to steel wall class A.

## EXECUTION

The door-frame is built of welded steel metallurgic and bended profiles. It is welded to steel wall. The door-leaf is made of two steel cassettes and inside frame of channel profile. The cassettes connected each other forms closed space filled of mineral wool.

Design of the door-leaf allows its making in two varieties :

- painted of stove paints (M),
- covered of PVC foil galvanized steel sheet (D)

The door is equipped with regulated driving system ( guiding rail, steel trucks, limiters opening of door ) protected with steel masking profile. Passage in clear opening of the door has also got covers. Door sill is protected with stainless steel cover. Closing device is standard made as bob hanged on steel line. A suitable weight of this bob ensures closing of the door-leaf in proper way. All is covered with steel masking profile.

## DELIVERY RANGE

In delivery range is included complete door with above mentioned equipment. Screws for installation of masking profiles and cylinder aren't included in delivery set.

## PACKING, TRANSPORT, STORAGE

The door is protected against mechanical damages and suitable for transport in containers. The goods placed on the pallets with wooden separators can be displaced by means of fork lift trucks and cranes. They have to be stored in roofed warehouse.

## DIVISION , MARKING AND FINISHING

Varieties :

P - right-hand door - as it is shown on drawing

L - left-hand door - as reflected

Finishing of door-leaf :

M - z/p - painted door-leaf acc. to RAL catalogue

D - z/p/d - door-leaf covered of PVC foil acc. to DOBEL or GISLAVED catalogue

z - colour from external side

p - colour from internal side

d - colour of profile around door-leaf for type D

Equipment :

- door with full escutcheon of lock - isn't marked in designation

Wp - door with escutcheon suitable for installation of cylinder

The door-frame is primed. All covers are painted acc. to RAL catalogue.

## EXAMPLE OF DESIGNATION

Sliding door class A60 of c.o. H x B – 1950x900, right variety (**P**), thick. of partition wall A=68, with escutcheon suitable for installation of cylinder (**Wp**), door-leaf covered of PVC foil (**D**), from external side (**z**) in colour B28C, from internal side (**p**) in colour A22A, profile around door-leaf (**d**) painted in colour RAL 9003, covers painted in colour RAL 9003.

SLIDING DOOR CLASS A60 1950x900-P/68-Wp-D zB28C/pA22A/d9003-9003 acc. to catalogue card  
no **KK 24-12/34-771**.

This catalogue card corresponds with drawing no N24-08/34-771.