



H	B	h		b	Mass (kg)
		I	II		
1850	800	1926	1962	912	59
	900			1012	66
1950	800	2026	2062	912	62
	900			1012	69
2021	800	2097	2133	912	64
	900			1012	71



## LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka  
 tel. +48/67/216-22-44  
 fax +48/67/216-59-40  
 e-mail: marketing@lubmor.pl  
 e-mail: konstrukcja@lubmor.pl

**STEEL DOOR**

**KI 24-90**  
**00-008**

# STEEL DOOR

## APPROPRIATION

Steel door is designed for closing the passages and entrances to special accommodations in hospitals and the other health service objects and for closing the passages in internal accommodations on all floating objects .

## EXECUTION

Specially profiled door-frame is made of 3 mm cold rolled stress free steel plate .

The anchors to building of the door in the wall may be welded to the door - frame type I .

Door sill is protected by means of a stainless steel cover .

The door-leaf is made of two cassettes and internal frame from channel section .

Every cassettes are made of 0,7 mm galvanized steel sheet .

All elements are connected by means of rivetting .

The door-leaf is filled with mineral wool .

The door may be equipped with window clear opening 400x600 of 6 mm hardened double glass pane .

The door is equipped with a mortise lock with symmetric patent insert 31/31 and stainless steel hinges .

## DELIVERY RANG

Delivery set includes a complete door with the fittings .

## PACKING , TRANSPORT , STORAGE

The doors are protected against mechanical damages by foil .

The products placed on pallets can be displaced by means of the fork-lift trucks and the cranes .

They can also be stored in rows and stacks in store accommodations .

## DIVISION , MARK AND FINISHING

Types :

I - without sill

II - with sill

Varieties :

P - right hand door

L - left hand door

Equipment :

- with mortise lock (no marked in designation)

S - with sanitary mortise lock

K - with the anchors to building

o - with window 400x600

The door is finished of white stove paint .

## EXAMPLE OF DESIGNATION

Steel door , clear opening HxB - 1950x800 type I - without sill , variety L - left , with the anchors to building - K , with window 400x600 - o .

STEEL DOOR 1950x800 I L - K - o acc. to information card no KI 24-90/00-008.