

Н	В	h		h	Mass
		I	II	b	(kg)
1850	1200	1926	1962	1312	79
	1500			1612	97
1950	1200	2026	2062	1312	83
	1500			1612	103
2021	1200	2097	2133	1312	86
	1500			1612	107



LUBMOR Ltd.

ul. Wieleńska 1, 64-980 Trzcianka

tel. +48/67/216-22-44 fax +48/67/216-59-40

e-mail: marketing@lubmor.pl e-mail: konstrukcja@lubmor.pl

DOUBLE-LEAF STEEL DOOR

KI 24-90 00-015

DOUBLE - LEAF STEEL DOOR

APPROPRATION

Double-leaf steel door is designed for closing the passages and entrances to special accommodations in hospitals and the other health service objects and for closing the passages in internal accommodations on all floating objects .

EXECUTION

Specially profiled door-frame is made of 3 mm cold rolled stress free steel plate.

The anchors to building of the door in the wall may be welded to the door-frame type I.

Door sill is protected by means of a stainless steel cover.

The door-leaves are made of two cassettes and internal frame from channel section.

Every cassettes are made of 0,7 mm galvanized steel sheet . All elements are connected by means of rivetting . The door-leaves are filled with mineral wool .

The door may be equipped with windows clear opening 400x600 of 6 mm hardened double glass pane .

The door is equipped with a mortise lock with symmetric patent insert 31/31, stainless steel hinges and two revolver bolts.

DELIVERY RANG

Delivery set includes a complete door with the fittings.

PACKING, TRANSPORT, STORAGE

The doors are protected against mechanical damages by foil and can be displaced by means of the fork-lift trucks and the cranes if will be placed on pallets .

The door can also be stored in rows and stacks in store accommodations.

DIVISION, MARK AND FINISHING

Types:

I - without sill

II - with sill

Varieties:

P - right hand door

L - left hand door

Equipment:

- with mortise lock (no marked in designation)

S - with sanitary mortise lock

K - with the anchors to building

o - with windows 400x600

The door is finished of white stove paint.

EXAMPLE OF DESIGNATION

Double-leaf steel door , clear opening HxB - 1950x1500 type I - without sill , variety L - left , with the anchors to building - K , with windows 400x600 - o .

DOUBLE - LEAF STEEL DOOR 1950x1500 I L-K-o acc. to information card no KI 24-90/00-015 .