

SHIP WINDOW CLASS A0

APPROPRATION

The ship windows class A0 are designed for using on the ships.

EXECUTION

The window is made acc.to Polish and international standards .

It is of steel frame, glass list and fireproof glass.

Glass list is screwed to the frame. A space between glass pane and the frame is filled with fire–proof insulation. A fire–proof glass pane is 10 mm thick . If the customer wish himself another thickness glass pane, it should be stated at the order.

Window frame is protected of epoxy primer thick. 40 μ m. The place covered of insulation is protected of painting set which consists a three epoxy layers of total thick. 100 μ m.

DELIVERY RANG

Delivery includes complete assemblied window .

PACKING, TRANSPORT, STORADE

The glass pane is protected with foil. This foil is removed after mounting of the window on the ship.

The windows are delivered on the pallets without packing. The goods should be transported of dry, clean and roofed trucks in order to avoid their dislocation and mechanical damages.

They should be stored in closed accommodations in order to ensure the same conditions like during transport and should also be protected against the agents which might to cause damages of the gaskets.

EXAMPLE OF MARKING

Ship window class A0 clear opening W x H – 800 x 1200. SHIP WINDOW CLASS A0 800 x 1200 acc.to no KK 24-07/30-270.

This catalogue card corresponds with drawing no N24-07/30-270.