

# **GRP EXTERNAL DOOR**

## APPROPRATION

The external door is designed for closing the pasageways form the open deck to the internal accomodations in all float objects . This door is suitable for mounting in metal partitions as a self – contained or combined door with heavy steel door .

## **EXECUTION**

The door frame is made of 3 mm specially profiled steel plate . The door leaf of sandwich construction is made of glass fibre reinforced polyester resin (GRP) with a core of rigid polyurethane foam .

The door sill is protected by means of stainless steel cover .

The door is fitted with a brass lock with patent insert and removable stainless steel hinges .

This door can also be fitted with rectangular vision panel of hardened glass pane .

The fittings are nickel – chromium plated and polished .

# **DELIVERY RANG**

Delivery comprises complete door with the fittings but without of mounting holes and fixing elements .

## PACKING, TRANSPORT, STORAGE

The door protected against mechanical damages is adapted for transportation in containers and displaces by means of the trucks and the cranes if the door are placed on pallets .

This door can also be stored in rows and stacks in store accomodations .

# DIVISION, MARK AND FINISHING

Varietes :

L - left hand door

P - right hand door

The door leaf is finished of polyester resin type gelcoat in standard colour white . The door frame in painted of a primer .

#### **EXAMPLE OF DESIGNATION**

GRP external door with panel , clear opening H x b - 1600 x 750 , variety L - left hand. GRP EXTERNAL DOOR 1600 x 750 L acc. to catalogue card no KK 24-12/34-211.

This catalogue card corresponds with drawing no N 24-90/34-211.