

DOUBLE LEAF INSIDE SLIDING DOOR

APPROPRATION

The sliding door is designed for closing internal accommodations in all float and land objects . They are suitable for mounting in metal and non – metal walls .

EXECUTION

The door – leaves of frame construction are made of Cape Marine Board (CMB) and glued on laminate type unilam , perstorp or veneer . Stainless steel channels are fixed around the door – leaves .

The door is equipped with sliding device which includes : upper mounting , bottom guidance . Sliding device bolt which ensures blocking the door – leaf in closed or opened position .

DELIVERY RANG

Delivery comprises the door with all fittings . The door hasn't the holes and fixing elements .

PACKING, TRANSPORT, STORAGE

The door is protected against mechanical damages . The goods can be displaced by means of the trucks and the cranes if they are placed on the pallets .

They can also be stored in rows or stacks .

DIVISION, MARK AND FINISHING

Varieties :

- P right hand door
- L left hand door

Finishing :

- U laminate type unilam
- P laminate type perstorp
- O veneer

EXAMPLE OF DESIGNATION

Double leaf inside sliding door , clear opening H x B -2050×1600 , variety P - right hand , faced both sides with laminate type unilam Wz -405 (imitation wood) .

DOUBLE LEAF INSIDE SLIDING DOOR 2050 x 1600 P - U / Wz - 405 acc. to information card no KI 24-95/34-331 .